Product Datasheet

Fine Quartz Sand

UZIN FINE SAND

Fire-cured quartz sand (0.3 - 0.8 mm grain size)

MAIN APPLICATION FIELD:

- for all reaction resin primers, e.g. UZIN PE 480, UZIN PE 481 or UZIN PE 404
- for all repair resins, e.g. UZIN KR 516
- for interior and exterior use

SUITABLE ON / FOR:

- creates gritted substrates to improve adhesion
- fills and adjusts the consistency

- creates gritted substrates to improve adhesion
- fills and adjusts the consistency

TECHNICAL DATA:

Packaging	bag
Pack size	25 kg
Colour	light grey

UZIN | A brand of Uzin Utz
DE | Uzin Utz SE | Dieselstrasse 3 | 89079 Ulm | Phone +49 731 4097-0 | Fax +49 731 4097-110 | info@uzin.de | www.uzin.de
GB | Uzin Utz UK Ltd. | Unit 2, Mitchell Court | Central Park, Rugby | CV23 0UY | Phone +44 1788 530 080 | Fax +44 1788 536 508 | uzin.uk@uzin-utz.com | www.uzin.co.uk

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

The use of barrier cream is recommended. When mixing wear a protective dust-mask. Refer to the notes on protection of the workplace and the environment in the Product Information Sheets for the other installation materials used.

DISPOSAL:

Where possible, collect product residues and re-use. Do not allow dispersal into drains, sewers or ground. Empty bags are recyclable.

The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. If in doubt, conduct a small test or obtain technical advice. Observe the installation recommendations of the covering manufacturer. The publication of this Product datasheet invalidates all previous Product Information. The respective updated version of this datasheet can be found on our website:www.uzin.co.uk