Product Datasheet

Rough Special Filler

UZIN XS 3.2

Fire-cured quartz mixture for creation of reaction resin screeds and mortars (0.1 - 3.2 mm grain size)

MAIN APPLICATION FIELD:

- creation of reaction resin screeds and mortars with UZIN PE 460
- for interior and exterior use

- premixed

TECHNICAL DATA:

Packaging	bag
Pack size	25 kg
Color	light grey

UZIN | A brand of UZIN UTZ
DE | Uzin Utz SE | Dieselstrasse 3 | 89079 Ulm | Telephone +49 731 4097-0 | Fax +49 731 4097-110 | E-Mail info@uzin.de | Internet www.uzin.de

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

The use of barrier cream is recommended. When mixing wear a protective dust-mask. Refer to the notes on protection of the workplace and the environment in the Product Information Sheets for the other installation materials used.

DISPOSAL:

Where possible, collect product residues and re-use. Do not allow dispersal into drains, sewers or ground. Empty bags are recyclable.

This product is intended exclusively for professional use by qualified commercial users. It must not be supplied to consumers. The above information is based on our experience and careful investigations. The variety of associated materials and different constructions and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. If in doubt, conduct a small test or obtain technical advice. Observe the installation recommendations of the floor covering manufacturer. The publication of this Product Data Sheet invalidates all previous product information. The respective updated version of this datasheet can be found on our website under www.uzin.com | 09/2026