Product Datasheet

Fleece inlay

CODEX AX 700 FLEECE

Fleece inlay for reinforcing codex AX 700

APPLICATIONS

Stable fleece insert for embedding in the liquid plastic codex AX 700. The use of codex AX 700 Fleece significantly increases the crack bridging and flexibility of the waterproofing.

SUITABLE FOR USE ON

- codex AX 700

PRODUCT BENEFITS/FEATURES

- Easy to cut
- High tensile strength
- Frost resistant
- UV-resistant

TECHNICAL SPECIFICATIONS

Pack type	roll
Pack size	30 m/roll
Shelf life	18 months
Color	white
Length	30 m
Width	15 cm 30 cm 50 cm
Thickness	approx. 0.7 mm
Area weight	approx. 110 g/m²

codex | A brand of Uzin Utz
GB | Uzin Utz UK Ltd. | Unit 2, Mitchell Court | Central Park, Rugby | Warwickshire, CV23 0UY | +44 1788 530 080 | codex.uk@uzin-utz.com | www.codex-x.com
DE | codex GmbH & Co. KG | Heuweg 5/1 | 89079 Ulm | +49 731 927093-0 | info@codex-x.com | www.codex-x.com

CODEX AX 700 FLEECE

SUBSTRATE PREPARATION

See codex AX 700

APPLICATION

1. codex codex AX 700 Fleece and cut to size. A joint overlap of at least 5 cm must be observed.
2. apply codex AX 700 and lay codex AX 700 Fleece into the fresh waterproofing and work over the entire surface until the fleece is saturated. Bond subsequent sheets with at least 5 cm overlap.
3. In the corner areas, embed codex AX 700 IE and codex AX 700 AE and also work over completely.
4. All fleece components must be completely saturated with codex AX 700.

PROTECTION OF THE WORKPLACE AND ENVIRONMENT

The product itself does not require any special labour protection measures. Refer to the notes on protection of the workplace and the environment in the Product Information Sheets for the other installation materials used.

DISPOSAL

Sleeves and carton packaging free from residues can be recycled. Material residues can be disposed of with domestic waste.

The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. If in doubt, conduct a small test or obtain technical advice. Observe the installation recommendations of the covering manufacturer. The publication of this datasheet invalidates all previous Information. The respective updated version of this datasheet can be found on our website: www.codex-x.com | 06/2024